

UNITED STATES PATENT AND TRADEMARK OFFICE  
**CERTIFICATE OF CORRECTION**

PATENT NO. : 7,018,517 B2  
APPLICATION NO. : 10/601185  
DATED : March 28, 2006  
INVENTOR(S) : Shinichi Kurita

Page 1 of 2

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Column 10, line 37, "a main body having sidewalls adapted to couple to at least" should be changed to "a main body having sidewalls coupled to at least"

Column 10, line 39, "chamber and to house at least a portion of a robot" should be changed to "chamber and housing at least a portion of a robot"

Column 10, Line 40, "adapted to transport a substrate between the at least one" should be changed to "that transports a substrate between the at least one"

Column 10, line 43, "a lid adapted to couple to and to seal a top portion of the" should be changed to "a lid that couples to and seals a top portion of the"

Column 10, line 45, "a domed bottom adapted to couple to and to seal a bottom" should be changed to "a domed bottom that couples to and seals a bottom"

Column 11, line 12, "a main body having sidewalls adapted to couple to at" should be changed to "a main body having sidewalls coupled to at"

Column 11, line 14, "lock chamber and to house at least a portion of a" should be changed to "lock chamber and housing at least a portion of a"

Column 11, line 15, "robot adapted to transport a substrate between the at" should be changed to "robot that transports a substrate between the at"

Column 11, line 18, "a lid adapted to couple to and to seal a top portion of" should be changed to "a lid that couples to and seals a top portion"

Column 11, line 20, "a domed bottom adapted to couple to and to seal a" should be changed to "a domed bottom that couples to and seals a"

Column 11, line 25, "the main body;" should be changed to "the main body; and"


Column 11, delete lines 26-29, which begin with "at least one processing chamber..." and end with "of the transfer chamber; and"

Column 11, line 31, "bottom into the transfer chamber, the robot adapted to" should be changed to "bottom into the transfer chamber, the robot"

Column 11, line 32, "transport a substrate between the at least one processing" should be changed to "transports a substrate between the at least one processing"

Column 12, line 2, "chamber adapted to couple at least one load lock chamber to" should be changed to "chamber coupled to at least one load lock chamber and to"

Signed and Sealed this  
Twenty-seventh Day of September, 2011



David J. Kappos  
*Director of the United States Patent and Trademark Office*

Column 12, line 9, “bottom is adapted to have a domed region with a radius” should be changed to “bottom has a domed region with a radius”

Column 12, line 12, “least a portion of a robot adapted to transfer substrates” should be changed to “least a portion of a robot that transfers substrates”

Column 12, line 18, “a main body having sidewalls adapted to couple to at least” should be changed to “a main body having sidewalls coupled to at least”

Column 12, line 20, “chamber and to house at least a portion of a robot” should be changed to “chamber and houses at least a portion of a robot”

Column 12, line 21, “adapted to transport a substrate between the at least one” should be changed to “that transports a substrate between the at least one”

Column 12, line 24, “a lid adapted to couple to and to seal a top portion of the” should be changed to “a lid that couples to and seals a top portion of the”

Column 12, line 26, “a domed bottom adapted to couple to and to seal a bottom” should be changed to “a domed bottom that couples to and seals a bottom”

Column 12, line 29, “a cylindrical region having a height adapted to accom-” should be changed to “a cylindrical region having a height that accom-”

Column 12, line 30, “modate at least a portion of an arm of a robot” should be changed to “modates at least a portion of an arm of a robot”

Column 12, line 48, “chamber adapted to couple at least one load lock chamber to” should be changed to “chamber coupled to at least one load lock chamber and to”

Column 12, line 53, “a cylindrical region having a height adapted to accom-” should be changed to “a cylindrical region having a height that accom-”

Column 12, line 54, “modate at least a portion of an arm of a robot” should be changed to “modates at least a portion of an arm of a robot”

Column 13, line 3, “a main body having sidewalls adapted to couple to at” should be changed to “a main body having sidewalls coupled to at”

Column 13, line 5, “lock chamber and to house at least a portion of a” should be changed to “lock chamber and housing at least a portion of a”

Column 13, line 6, “robot adapted to transport a substrate between the at” should be changed to “robot that transports a substrate between the at”

Column 13, line 9, “a lid adapted to couple to and to seal a top portion of” should be changed to “a lid that couples to and seals a top portion of”

Column 13, line 11, “a domed bottom adapted to couple to and to seal a” should be changed to “a domed bottom that couples to and seals a”